

Evaporative Air Coolers



The Whirlpool 214 CFM indoor evaporative air cooler offers an effective, low cost cooling option in areas with dry heat, such as the southwest region of the United States. The low power consumption of a mere 110 watts will save you a noteworthy amount on your energy bill in comparison to the cost of running a standard air conditioner. This unit is designed for indoor use in open environments equipped with cross ventilation up to 425 square feet. Three fan speeds and automatic louvers evenly distribute cool air after it is sifted through the filter, providing a fresh, clean breeze throughout your room. For those living in more humid climates, consider Whirlpool's portable air conditioning units or window air conditioners.



MODEL	WPEC12GT	WPEC12GW	WPEC12RGT	WPEC12RGW
PERFORMANCE				
Color	Titanium	White	Titanium	White
Cooling Range (Sq. Ft.)	428-sq. ft.	428-sq. ft.	428-sq. ft.	428-sq. ft.
Water Tank Volume	12 pint	12 pint	12 pint	12 pint
Air Flow (CFM):	214	214	214	214
Noise Rating (dBA):	56	56	56	56
Remote Control	No	No	Yes	Yes
Ice Pack	No	No	Yes	Yes
Castor Wheels	Yes	Yes	Yes	Yes
ELECTRICAL RATINGS				
Voltage (V) / Frequency (Hz)	120 V / 60 Hz	120 V / 60 Hz	120 V / 60 Hz	120 V / 60 Hz
Cooling Amps	.92 A	.92 A	.92 A	.92 A
Cooling Watts	110 W	110 W	110 W	110 W
FEATURES				
Control Type	Light Touch	Light Touch	Light Touch	Light Touch
Filter Clean Indicator	No	No	No	No
Sleep Mode	Yes	Yes	Yes	Yes
Number of Cooling Speeds	3	3	3	3
Power Saver Mode	No	No	No	No
Programmable Timer	1, 2, 4, or 8 Hours	1, 2, 4, or 8 Hours	1, 2, 4, or 8 Hours	1, 2, 4, or 8 Hours
Full Closing Louvers	Yes	Yes	Yes	Yes
Water Tank Full Alert	Yes	Yes	Yes	Yes
Fan Only Mode	Yes	Yes	Yes	Yes
Multiple Air Direction Control	Yes	Yes	Yes	Yes
Auto Air Swing Mode	Yes	Yes	Yes	Yes
Removable Air Filter	Yes	Yes	Yes	Yes
DIMENSIONS / WEIGHT				
Product Dimensions (in.)	16.5x13.4x31.5	16.5x13.4x31.5	16.5x13.4x31.5	16.5x13.4x31.5
Product Weight (lb.)	16.84	16.84	16.84	16.84
Warranty	1 Year Limited	1 Year Limited	1 Year Limited	1 Year Limited
UL Code	UL 507	UL 507	UL 507	UL 507
UPC Code	192487072707	192487072714	192487072745	192487072752



*Included with "R" Models